



MATERIAL SAFETY DATA SHEET

ALUBAND FLASHING TAPE

1: IDENTIFICATION OF MATERIAL AND SUPPLIER

PRODUCT NAME: ALUBAND FLASHING TAPE

SUPPLIER: **Thermakraft Pty Ltd**
19 Elliot Place P.O. Box 6016
Ringwood Ringwood
Victoria 3134 East Victoria 3134
Australia Australia
Email: sales@thermakraft.com.au Website: www.thermakraft.com.au
TEL: 0 3 9870 5880
FAX: 0 3 9870 5990

2: COMPOSITION/INFORMATION ON INGREDIENTS

COMPOSITION: Laminated product based on Aluminum /polymeric sheet backing film.
Bituminous adhesive manufactured from asphalt with resins, release film
This product is not classified as hazardous under normal use.

3: HEALTH AND PERSONAL PROTECTION DATA

EYE CONTACT: If particles enter the eye, they will cause irritation possibly resulting in stretching of the eye, stinging, redness. Wear safety goggles where there is danger of eye contact.

SKIN CONTACT: Irritations of the skin are possible from the bituminous adhesive. Clean affected area with soap and water. No specific hand protection noted.

INGESTION: Typically asphalt products have low toxicity when swallowed. If swallowed this product may cause irritation of the digestive tract. Obtain medical advice

INHALATION: Not normally an issue, use of product in ventilated working areas is not expected to cause adverse effects. If product is heated, exposure to resultant fumes or vapour may cause irritation of the nose and throat. Move the exposed person to fresh air.

HYGIENIC WORK ROUTINES: Wash hands at the end of work shift and before eating or smoking.

4: FIRE FEIGHTING MEASURES

EXTINGUISHER MEDIA: Foam, CO₂, Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURE: Wear self-contained breathing apparatus. Combustion creates: Asphyxiating gases/vapour. Use

extinguishing media appropriate for surrounding area

5: HANDLING AND STORAGE

HANDLING: This product is not classified as hazardous under normal use.

STORAGE: Store at moderate temperatures in dry areas, away from heat and all ignition sources, open flames.

6: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Metallic looking foil with black bituminous modified adhesive on reverse side.

SOLUBILITY: Insoluble in water

7: STABILITY AND REACTIVITY

STABILITY: Normally stable

MATERIALS TO AVOID: Strong oxidizing agents

8: ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS: Not regarded as dangerous for the environment.

9: DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

10: TRANSPORT INFORMATION

ROAD:

HAZARD CLASS: Not classified for transport

ROAD TRANSPORT NOTES: Not classified for transport

RAIL:

RAIL TRANSPORT NOTES: Not classified for transport

SEA/AIR:

Not classified for transport

11: OTHER INFORMATION

NOTE: This information herein has been based upon current scientific data. It is intended for use by skilled persons at their own risk. Thermakraft Pty Ltd does not assume responsibility for events resulting or damages incurred from its use. The information cited in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Issue Date: September 2017

Revision Due: September 2020

Issue No: 3

Issued by: **Thermakraft Pty** 19 Elliot Place, Ringwood, Victoria 3134 Australia