



Product Data Sheet

PVC AUSMESH

PVC coated roof safety mesh

Polyvinyl Chloride (PVC) coated Ausmesh is a robust roof underlay support and fall safety mesh for use on a variety of commercial buildings. PVC Ausmesh is constructed of high tensile galvanised wire exceeding 450MPa and coated with a layer of PVC. When used for roofing becomes a permanent fixture in the building.

PVC coated Ausmesh is 1800mm wide and can be cut to length for efficiency:

1800mm x 50m	Available cut to length*	Available in Black and White PVC coating
--------------	--------------------------	--

* **Note:** Production time allowance may vary - contact your Thermakraft Representative for more information.

Smarter products. Better buildings.
thermakraft.com.au



PVC Ausmesh

PVC coated roof safety mesh

Product Description

Width	Mesh Size	Wire Diameter	Tensile Strength	Wire Coating	Length	Weight
1800mm	300mm x 150mm	2mm galvanised	Crosswire/ Transverse Wire min 450MPa	Standard AS/NZS 4534:2006 WO2	Standard roll size 50m	1800 width = ~27kg per roll.
			Line Wire/ Longitudinal Wire min 500 MPa			

Scope of Use

- Roof safety mesh as a primary means for fall protection when working at heights in domestic, commercial and industrial building applications that use steel or timber structure.
- Suitable for the support of foil underlays in exposed roof spaces, and synthetic underlays (Thermakraft Covertek 407) in enclosed or exposed roof spaces.
- May be used to support insulation. Usage intent and compatibility must be checked by the designer with the insulation manufacturer.
- May be used for coastal builds, exposed structures or buildings that require roof safety mesh to achieve specific aesthetic criteria.

General

- Constructed of 2mm high tensile galvanised steel wire. Formed mesh is coated with a layer of PVC.
- Longitudinal wires are spaced at 150mm centres with cross wires spaced at 300mm centres forming a rectangular shape.
- Roof application only for fall protection and underlay support.

Product Limitations

- NOT to be exposed to sunlight, dust, rain or other weather elements for more than 7 days. Recommended same day coverage by roof cladding.

Compliance

- PVC Ausmesh complies to AS/NZS 4389:2015 standard (Roof Safety Mesh).

Durability

Meets the Performance Requirements outlined in AS/NZS 4389:2015 standard provided that;

- It is not damaged.
- It is only used in accordance with the Product Limitations set out on this Product Data Sheet.
- It is installed in accordance with the written instructions.
- It is installed by or under supervision of a Licensed or Registered Builder in the relevant state or territory's building authority.
- It is compatible with building structure materials used*.

* **Note:** Specifiers and product user must test for building structure materials' compatibility with PVC coated Ausmesh before installation.

For advice or information regarding Thermakraft products refer to Thermakraft literature or contact **1800 960 338**, visit **thermakraft.com.au** or follow the **QR code**.

Thermakraft Australia Pty Limited / 1800 960 338

Smarter products. Better buildings.
thermakraft.com.au

